



Make Model	Case IH Farmall 55 C	Case IH Farmall 65 C	Case IH Farmall 75 C
<b>Engine</b>			
Number of cylinders	4	4	4
Type	Common Rail Diesel engine, turbocharged	Common Rail Diesel engine, turbocharged	Common Rail Diesel engine, turbocharged
Emission Level	Stage IIIB	Stage IIIB	Stage IIIB
Capacity (cm <sup>3</sup> )	3,400	3,400	3,400
<b>Engine Performance</b>			
Rated engine power (hp (kW))	58 (43)	65 (48)	75 (55)
Rated engine speed (rpm)	2,300	2,300	2,300
Maximum torque (Nm?@ rpm)	244 @ 1,500	275 @ 1,500	309 @ 1,500
Torque rise Standard and Power Management (%)	37 / -	38 / -	36 / -
Fuel tank capacity diesel / urea (litres)	90 (-)	90 (-)	90 (-)
<b>Standard Transmission</b>			
Transmission Type	12 x 12 Synchroshift with mechanical shuttle	12 x 12 Synchroshift with mechanical shuttle	12 x 12 Synchroshift with mechanical shuttle
Maximum Forward Speed (kp/h)	30 / 40	30 / 40	30 / 40
Powershuttle	-	-	-
Creeper	-	-	-
<b>Optional Transmission 1</b>			
Transmission Type	12 x 12 Synchroshift	12 x 12 Synchroshift	12 x 12 Synchroshift
Maximum Speed Forward (kp/h)	30 / 40	30 / 40	30 / 40
Powershuttle	Std.	Std.	Std.
Creeper	-	-	-
<b>Optional Transmission 2</b>			
Transmission Type	20 x 20 Synchroshift with mechanical shuttle	20 x 20 Synchroshift with mechanical shuttle	20 x 20 Synchroshift with mechanical shuttle
Maximum Speed Forward (km/h)	30 / 40	30 / 40	30 / 40
Powershuttle	-	-	-
Creeper	Std.	Std.	Std.
<b>Optional Transmission 3</b>			
Transmission Type	20 x 20 Synchroshift	20 x 20 Synchroshift	20 x 20 Synchroshift
Maximum Speed Forward (km/h)	30 / 40	30 / 40	30 / 40
Powershuttle	Std.	Std.	Std.
Creeper	Std.	Std.	Std.
<b>Power Take Off</b>			
PTO Type	electro-hydraulic engagement	electro-hydraulic engagement	electro-hydraulic engagement
Speed Standard @ rpm	540	540	540
Speed Optional @ rpm	540 / 540E	540 / 540E	540 / 540E
Ground drive	Option	Option	Option
Shaft type	-	-	-
<b>Front PTO and hitch</b>			
Speed Standard @ rpm	-	-	-
Front hitch lift capacity (kg)	-	-	-
<b>Drive and Steering (Driveline)</b>			
2WD	Yes	Yes	Yes
4WD	Yes	Yes	Yes
Front axle suspension	-	-	-
Min.turning radius?(m)	3,82	3,82	3,82
Rear axle diff-lock	Self-lock	Self-lock	Self-lock
Service Brake Type	-	-	-
ABS Anti-lock braking system	-	-	-
<b>Hydraulic System</b>			
System Type	electro-hydraulic engagement	electro-hydraulic engagement	electro-hydraulic engagement
Max. pump flow rate Standard / Option (Litres)	84	84	84
Control type	Mechanical Hitch Control (MHC)	Mechanical Hitch Control (MHC)	Mechanical Hitch Control (MHC)
Max. lift capacity (kg)	2,500	2,500	2,500
OECD lift capacity through range @ 610 mm (kg)	2,100	2,100	2,100
Max. number of rear remotes valves	3	3	3
Max. number of mid mount valves	2	2	2



Make Model	Case IH Farmall 85 C	Case IH Farmall 95 C	Case IH Farmall 105 C	Case IH Farmall 115 C
<b>Engine</b>				
Number of cylinders	4	4	4	4
Type	Common Rail Diesel engine, turbocharged and intercooled	Common Rail Diesel engine, turbocharged and intercooled	Common Rail Diesel engine, turbocharged and intercooled	Common Rail Diesel engine, turbocharged and intercooled
Emission Level	Stage IIIB	Stage IIIB	Stage IIIB	Stage IIIB
Capacity (cm <sup>3</sup> )	3,400	3,400	3,400	3,400
<b>Engine Performance</b>				
Rated engine power (hp (kW))	86 (63)	99 (73)	107 (79)	114 (84)
Rated engine speed (rpm)	2,300	2,300	2,300	2,300
Maximum torque (Nm@ rpm)	351 @ 1,500	407 @ 1,500	444 @ 1,500	457 @ 1,500
Torque rise Standard and Power Management (%)	34 / -	34 / -	35 / -	32 / -
Fuel tank capacity diesel / urea (litres)	115 (-)	115 (-)	115 (-)	115 (-)
<b>Standard Transmission</b>				
Transmission Type	12 x 12 Synchroshift with powershuttle	12 x 12 Synchroshift with powershuttle	12 x 12 Synchroshift with powershuttle	12 x 12 Synchroshift with powershuttle
Maximum Forward Speed (kp/h)	30 / 40	30 / 40	30 / 40	30 / 40
Powershuttle	Std.	Std.	Std.	Std.
Creeper	-	-	-	-
<b>Optional Transmission 1</b>				
Transmission Type	24 x 24 Synchroshift with splitter	24 x 24 Synchroshift with splitter	24 x 24 Synchroshift with splitter	24 x 24 Synchroshift with splitter
Maximum Speed Forward (kp/h)	30 / 40	30 / 40	30 / 40	30 / 40
Powershuttle	Option	Option	Option	Option
Creeper	-	-	-	-
<b>Optional Transmission 2</b>				
Transmission Type	24 x 24 or 40 x 40 2-speed Powershift	24 x 24 or 40 x 40 2-speed Powershift	24 x 24 or 40 x 40 2-speed Powershift	24 x 24 or 40 x 40 2-speed Powershift
Maximum Speed Forward (km/h)	40	40	40	40
Powershuttle	Std.	Std.	Std.	Std.
Creeper	Option	Option	Option	Option
<b>Optional Transmission 3</b>				
Transmission Type	20 x 20 Synchroshift	20 x 20 Synchroshift	20 x 20 Synchroshift	20 x 20 Synchroshift
Maximum Speed Forward (km/h)	30 / 40	30 / 40	30 / 40	30 / 40
Powershuttle	Option	Option	Option	Option
Creeper	Option	Option	Option	Option
<b>Power Take Off</b>				
PTO Type	electro-hydraulic engagement	electro-hydraulic engagement	electro-hydraulic engagement	electro-hydraulic engagement
Speed Standard @ rpm	540	540	540	540/540 E
Speed Optional @ rpm	540/540E or 540E/1,000 or 540/1000 or 540/ 540E/1000	540/540E or 540E/1,000 or 540/1000 or 540/ 540E/1000	540/540E or 540E/1,000 or 540/1000 or 540/ 540E/1000	540/1,000 or 540E/1,000 or 540/540E/1000
Ground drive	Option	Option	Option	Option
Shaft type	-	-	-	-
<b>Front PTO and hitch</b>				
Speed Standard @ rpm	1,000 @ 1,920	1,000 @ 1,920	1,000 @ 1,920	1,000 @ 1,920
Front hitch lift capacity (kg)	1,670	1,670	1,670	1,670
<b>Drive and Steering (Driveline)</b>				
2WD	Yes	Yes	Yes	Yes
4WD	Yes	Yes	Yes	Yes
Front axle suspension	-	-	-	-
Min.turning radius?(m)	4,33	4,33	4,33	4,33
Rear axle diff-lock	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Service Brake Type	-	-	-	-
ABS Anti-lock braking system	-	-	-	-
<b>Hydraulic System</b>				
System Type	Open Center	Open Center	Open Center	Open Center
Max. pump flow rate Standard / Option (Litres)	100	100	100	100
Control type	Electronical Hitch Control (EHC)	Electronical Hitch Control (EHC)	Electronical Hitch Control (EHC)	Electronical Hitch Control (EHC)
Max. lift capacity (kg)	4400	4400	4400	4400
OECD lift capacity through range @ 610 mm (kg)	4270	4270	4270	4270
Max. number of rear remotes valves	3	3	3	3
Max. number of mid mount valves	2	2	2	2